## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		, , ,	J	0, 0
Supplier's nam	e or trade mark:	sera GmbH, Heinsl	berg	
Supplier's add	ress: Engineering	department, Borsi	gstr. 49, 52525 Heinsberg	g, DE
Model identific	er: sera LED chip t	tropic sun, #31174		
Type of light so	ource:			
Lighting techno	ology used:	LED	Non-directional or directional:	NDLS
Light source cap-type		G4		
(or other electric interface)				
Mains or non-r	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneabl	e light source:	No	Envelope:	-
High luminance	e light source:	No		
Anti-glare shield:		No	Dimmable:	Yes
		Product para	ameters	
Parameter		Value	Parameter	Value
		General product	<u>-</u>	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		1	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		71 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 300
On-mode expressed in W	power (P <sub>on</sub> ),	1,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	14	Spectral power	See image
dimensions without	Width	37	distribution in the	in last page
	Depth	37		Page 1 /

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,338			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-19	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

